






AT 6.4 SA DS

| Cutting Capacity | 90° | 45°DX-R | 60°DX-R | 45°SX-L | 60°SX-L |
|---|-------------|-------------|---------|-------------|---------|
|  in | 15.5 | 15.5 | 12 | 15.5 | 12 |
|  in | 15.5 | 15.5 | 12 | 15.5 | 12 |
|  in | 23.5 x 15.5 | 15.5 x 15.5 | 12 x 12 | 15.5 x 15.5 | 12 x 12 |
|  in | 23.5 x 8 | - | - | - | - |
|  in | 23.5 x 15.5 | - | - | - | - |

| | | |
|------------------------------|---|-----------------------|
| Blade Dimensions | ▶ | 249.5 x 1.5 x 0.05 in |
| Working Height | ▶ | 35.5 in |
| Blade Motor Power | ▶ | 5 hp |
| Cooling Pump Motor Power | ▶ | 0.16 hp |
| Hydraulic Pump Motor Power | ▶ | 2 hp |
| Blade Speed | ▶ | 65 ÷ 328 ft/min |
| Cutting Downfeed | ▶ | 0 ÷ 8 in/min |
| Fast Downfeed | ▶ | 98.5 in/min |
| Coolant Tank Capacity | ▶ | 39.5 gal |
| Hydraulic Unit Tank Capacity | ▶ | 8 gal |
| Overall Dimensions (approx.) | ▶ | 121 X 135 X 98 in |
| Weight (approx.) | ▶ | 6834 lbs |